soleluna mario nanni 2010

apparecchio di illuminazione da terra per esterni IP67.
realizzato con profilo in acciaio inox AISI 316L sezione 17x45mm.
modelli:
soleluna circolare diametro Ø454mm h.45mm, cablato con sorgente elettronica 3000K 13W 1248lm,
soleluna semicircolare 454x227mm h.45mm, cablato con sorgente elettronica 3000K 6W 576lm.
alimentatore escluso, da installare remoto.
finiture: acciaio inox lucido.

IP67 rated floor-standing light fitting for outdoor use.
made of AISI 316L stainless steel profile with 17x45mm section.
versions:
soleluna circolare Ø454mm h.45mm wired with 3000K 13W 1248lm led source,
soleluna semicircolare 454x227mm h.45mm wired with 3000K 6W 576lm led source.
power supply not included, to be installed remotely.
finishes: polished stainless steel.





soleluna | **24Vdc** | **IP67**

a6.504.01 circolare — inox 316L lucido / polished 316L stainless steel — 3000K 13W 4,5

Ra	ies tm/30		sdcm	Vf	lm/m	W/m	lm/W	
80	Rf 83	Rg 95	step 3	24	520	10	52	**A**
V1031	9	Ta25 °C	vita media · average life		50000 h		L80	B10

soleluna circolare





a6.504.03 semicircolare — inox 316L lucido / polished 316L stainless steel — 3000K 6W 1,6

Ra	ies tm/30		sdcm	Vf	lm/m	W/m	lm/W	
80	Rf 83	Rg 95	step 3	24	520	10	52	**A**
V1031	9	Ta25 °C	vita media · average life		50000 h		L80	B10

soleluna semicircolare



cavi con connettore femmina m8. cables with m8 female connector. **IP67**

f9.250.71 150mm 0,01

cavi con connettori m/f m8. cables with m8 m/f connectors. **IP67**

f9.250.72 2000mm 0,1

f9.250.73 5000mm 0,3

f9.250.74 10000mm 0,6

sistema di derivazione tensione continua. dc derivation hub.



f9.250.79 con 6 connettori femmina +1 connettore maschio m8 / with 6 female connectors +1male connector m8 — 0,1





Subscribe To Our Newsletter

Cirrus Lighting

Distributor for Viabizzuno
Architectural Lighting Solutions
Web: www.cirruslighting.co.uk
Email: sales@cirruslighting.co.uk
Tel: 0207 193 2175
Fax: 0207 193 3175