



apparecchio di illuminazione da terra per interni ed esterni IP67. realizzato in alluminio peraluman, dimensioni 280x280mm h.218mm modelli:

vase con vetro antiurto

IK10 trasparente.

vase con vetro antiurto

IK10 sabbiato.

kit asimmetrico e kit simmetrico cablati con sorgente elettronica Ra97 3000K 2x22,1W 3490lm. kit spot orientabile cablato con sorgente elettronica Ra98 30,5W 3000lm.

ottiche: asimmetrica, simmetrica, 18°, 28°, 42°.

alimentatore 120-240V 50-60Hz incluso.

accessori: alette frangiluce

orientabili, cavo con

interruttore e spina.

finiture: alluminio peraluman, bruno antico, scurodivals.

IP67 rated floor-standing light fitting for indoor and outdoor use. made of peraluman aluminium, size 280x280mm h.218mm versions:

vase with trasparente

IK10 shock-resistant glass.

vase with sanded

IK10 shock-resistant glass.

asymmetrical and symmetrical

kits wired with Ra97 3000K

2x22,1W 3490lm led source.

adjustable kit spot with Ra98

30.5W 3000lm led source.





optics: asymmetrical, symmetrical, 18°, 28°, 42°.

120-240V 50-60Hz power supply included.

accessories: adjustable anti-glare louvres, cable with switch and plug.

finishes: peraluman aluminium, antique brown, scurodivals.





vase trasparente



IP67 IK10



Vb4.003.30	alluminio peraluman · peraluman aluminium	6
Vb4.003.31	bruno antico · antique brown	6
Vb4.003.32	scurodivals	6


vase sabbato



IP67 IK10




Vb4.003.35	alluminio peraluman · peraluman aluminium	6
Vb4.003.36	bruno antico · antique brown	6
Vb4.003.37	scurodivals	6



kit asimmetrico	120-240V 50-60Hz	A	K	⊕	⚠	CE	i
------------------------	-------------------------	----------	----------	---	---	----	---

Vb9.003.81 3000K 2x22,1W 2,2


Ra	R9	ies tm-30		sdc	mA	V _{f (min)}	lm	W	lm/W	
97	90	Rf 96	Rg 100	step 2	900	24,6	3490	44,2	79	A
dz011-2	10	Ta25 °C		vita media · average life		50000 h	L80 B10			



kit simmetrico	120-240V 50-60Hz	A	K	⊕	⚠	CE	i
-----------------------	-------------------------	----------	----------	---	---	----	---

Vb9.003.83 3000K 2x22,1W 2,2

Ra	R9	ies tm-30		sdc	mA	V _{f (min)}	lm	W	lm/W	
97	90	Rf 96	Rg 100	step 2	900	24,6	3490	44,2	79	A
dz011-2	10	Ta25 °C		vita media · average life		50000 h	L80 B10			




kit spot	120-240V 50-60Hz	A	K	⊕	⚠	CE	i
-----------------	-------------------------	----------	----------	---	---	----	---

Vb9.003.85 3000K 30,5W 18° 2

Vb9.003.86 3000K 30,5W 28° 2


Vb9.003.87 3000K 30,5W 42° 2

Ra	R9	ies tm-30		sdc	mA	V _{f (min)}	lm	W	lm/W	
98	98	Rf 96	Rg 103	step 1	1050	29,0	3000	30,5	98	A+
xm001	les19	Ta25 °C		vita media · average life		70000 h	L80 B10			



accessori. accessories.	CE	i
--------------------------------	----	---

f9.002.08 alette frangiluce orientabili · adjustable louvre 0,5



f9.002.09 cavo con interruttore e spina IP20 0,2
cable with switch and plug





Subscribe To Our Newsletter



**Distributor for Viabizzuno
Architectural Lighting Solutions**

Web: www.cirruslighting.co.uk

Email: sales@cirruslighting.co.uk

Tel: 0207 193 2175

Fax: 0207 193 3175

