

big feet mario nanni 1995



apparecchio di illuminazione da terra per interni ed esterni IP67. realizzato in alluminio peraluman, dimensioni massime 280x280mm h.338mm, completo di 4 piedi.

modelli:

big feet con vetro antiurto IK10 trasparente.

big feet con vetro antiurto IK10 sabbiato.

kit asimmetrico e kit simmetrico cablati con sorgente elettronica Ra97 3000K 2x22,1W 3490lm.

kit spot orientabile cablato con sorgente elettronica Ra98 30,5W 3000lm.

ottiche: asimmetrica, simmetrica, 18°, 28°, 42°. alimentatore 120-240V 50-60Hz incluso.

accessori: alette frangiluce orientabili, cavo con interruttore e spina.

finiture: alluminio peraluman, bruno antico, scurodivals.

IP67 rated floor-standing light fitting for indoor and outdoor use.

made of peraluman aluminium, maximum size 280x280mm h.338mm, with 4 feet.

versions:

big feet with transparent IK10 shock-resistant glass.

big feet with sanded IK10 shock-resistant glass.

asymmetrical and symmetrical kits wired with Ra97 3000K 2x22,1W 3490lm led source.

adjustable kit spot with Ra98 30.5W 3000lm led source.





optics: asymmetrical, symmetrical, 18°, 28°, 42°.

120-240V 50-60Hz power supply included.

accessories: adjustable anti-glare louvres, cable with switch and plug.

finishes: peraluman aluminium, antique brown, scurodivals.





big feet trasparente



IP67 IK10 ☆ CE



- | | | |
|-------------------|---|---|
| Vb4.003.20 | alluminio peraluman · peraluman aluminium | 7 |
| Vb4.003.21 | bruno antico · antique brown | 7 |
| Vb4.003.22 | scurodivals | 7 |

big feet sabbiato




IP67 IK10 ☆ CE




- | | | |
|-------------------|---|---|
| Vb4.003.25 | alluminio peraluman · peraluman aluminium | 7 |
| Vb4.003.26 | bruno antico · antique brown | 7 |
| Vb4.003.27 | scurodivals | 7 |







kit asimmetrico		120-240V 50-60Hz		A	K	\oplus	\triangle	CE	i	
Vb9.003.81	3000K					2x22,1W	2,2			
Ra	R9	ies tm-30		sdc	mA	V _{f(min)}	lm	W	lm/W	
97	90	Rf 96	Rg 100	step 2	900	24,6	3490	44,2	79	A
dz011-2	¹⁰	Ta25 °C		vita media · average life		50000 h	L80 B10			




kit simmetrico		120-240V 50-60Hz		A	K	\oplus	\triangle	CE	i	
Vb9.003.83	3000K					2x22,1W	2,2			
Ra	R9	ies tm-30		sdc	mA	V _{f(min)}	lm	W	lm/W	
97	90	Rf 96	Rg 100	step 2	900	24,6	3490	44,2	79	A
dz011-2	¹⁰	Ta25 °C		vita media · average life		50000 h	L80 B10			



kit spot		120-240V 50-60Hz		A	K	\oplus	\triangle	CE	i	
Vb9.003.85	3000K					30,5W	18°	2		
Vb9.003.86	3000K					30,5W	28°	2		
Vb9.003.87	3000K					30,5W	42°	2		
Ra	R9	ies tm-30		sdc	mA	V _{f(min)}	lm	W	lm/W	
98	98	Rf 96	Rg 103	step 1	1050	29,0	3000	30,5	98	A+
xm001	les19	Ta25 °C		vita media · average life		70000 h	L80 B10			



accessori. accessories.		CE	i
f9.002.08	alette frangiluce orientabili · adjustable louvre	0,5	



f9.002.09	cavo con interruttore e spina IP20 cable with switch and plug	0,2
------------------	--	-----





Subscribe To Our Newsletter



**Distributor for Viabizzuno
Architectural Lighting Solutions**

Web: www.cirruslighting.co.uk

Email: sales@cirruslighting.co.uk

Tel: 0207 193 2175

Fax: 0207 193 3175

