eco mini track mario nanni 2015

apparecchio di illuminazione a binario per interni IP20.
realizzato in alluminio ossidato e verniciato a polvere, composto da un faretto diametro Ø55mm h.69mm fissato ad un adattatore tramite un giunto di rotazione, orientabile di 360° sull'asse verticale e di 90° su quello orizzontale.
cablato con sorgente elettronica les6 12,4W o les14 17,4W con 2700K fino a 1680lm o 3000k fino a 1796lm.
ottiche: 13° 19° 36°
alimentatore 220-240V 50-60Hz incluso.
finiture: my bianco, nero55.

IP20 rated track-mounted light fitting for indoor use.
made of powder coated oxidized aluminium, consisting of diameter Ø55mm h.69mm spotlight fixed to an adapter through a turning joint, adjustable by 360° on the vertical axis and by 90° on the horizontal axis.
wired with les6 12,4W or les14 17,4W 2700K up to 1680lm or 3000K up to 1796lm led source.
optics: 13° 19° 36°
spotlight 220-240V 50-60Hz included.
finishes: my bianco, nero55.



eco mini track	220-240V 50-60Hz	A	IP20			
Vb7.579.11.27	my bianco			2700K	13°	0,7
Vb7.579.12.27	nero55			2700K	13°	0,7

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	700	17,8	767	12,4	62	**A**
cd010	les6 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

Vb7.579.11.30	my bianco					3000K	13°	0,7	
Vb7.579.12.30	nero55					3000K	13°	0,7	

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	700	17,8	826	12,4	66	**A**
cd011	les6 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

gradi di apertura fascio luminoso 13°
beam's angle degrees







eco mini track	220-240V 50-60Hz	A	IP20			
Vb7.579.13.27	my bianco			2700K	19°	0,7
Vb7.579.14.27	nero55			2700K	19°	0,7

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	500	34,8	1680	17,4	97	**A+**
ci000	les14 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

Vb7.579.13.30	my bianco					3000K	19°	0,7	
Vb7.579.14.30	nero55					3000K	19°	0,7	

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	500	34,8	1796	17,4	103	**A+**
ci001	les14 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

gradi di apertura fascio luminoso 19°
beam's angle degrees





gradi di apertura fascio luminoso 36°
beam's angle degrees







eco mini track	**220-240V 50-60Hz**	**IP20**		
Vb7.579.15.27	my bianco		2700K	36° 0,7
Vb7.579.16.27	nero55		2700K	36° 0,7

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	500	34,8	1680	17,4	97	**A+**
ci000	les14 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

Vb7.579.15.30	my bianco					3000K	36°	0,7	
Vb7.579.16.30	nero55					3000K	36°	0,7	

Ra	ies tm-30		sdcm	mA	$V_{f\,(min)}$	lm	W	lm/W	
95	Rf 92	Rg 100	step 2	500	34,8	1796	17,4	103	**A+**
ci001	les14 ●	Ta25 °C	vita media · average life			50000 h		L70	B10

accessori. accessories.

Vb9.580.91 frangiluce nido d'ape · louvre honeycomb 0,01

Vb9.580.92 lente ellittica · elliptical lens 0,04





Subscribe To Our Newsletter

Cirrus Lighting

Distributor for Viabizzuno
Architectural Lighting Solutions
Web: www.cirruslighting.co.uk
Email: sales@cirruslighting.co.uk
Tel: 0207 193 2175
Fax: 0207 193 3175